

**POMPE A GIRANTE FLESSIBILE
FLEXIBLE IMPELLER PUMPS
BOMBAS CON RODETE FLEXIBLE**

TIFONE
"FL" 900 rpm



Adatta per il travaso di vino, mosti senza raspi e liquidi alimentari in genere. Le versioni T-12, T-25, T-40, T-70 sono particolarmente indicate per il riempimento di damigiane e contenitori. L'aspirazione è ambivalente nei due sensi di rotazione. La girante in gomma evita di sbattere i vini travasati. Funziona a basso numero di giri con flusso omogeneo e continuo e per il suo principio di funzionamento si può definire una pompa a "pistone rotante".

Suitable for decanting wine and alimentary liquids, T-25, T-40, T-70 are indicated for filling demi-johns and tanks in general. Suction is available on both directions. The rubber impeller prevents the shaking of the decanted liquids. All pumps work at low r.p.m., the flow is steady and quite gentle and according to its principle of working this pump can be called a "rotary piston pump".



I MODELLI A PARTIRE DALLA T-110 SONO PARTICOLARMENTE INDICATI PER IL TRAVASO DI DIRASPATO

MODELS FROM T-110 ARE PARTICULARLY SUGGESTED FOR THE TRANSFER OF DESTEMMED GRAPES.

MOD.	R.P.M.	Q (HL/h) a 0 Bar	A x B x H	KG	MAX Bar	CONNECTORS	MOTOR
T-12	900	12 HL/h	300x210x200	9	2	Ø25	1-Phase 0,5 HP 3-phase 0,6 HP
T-25/FL	900	22 HL/h	325x210x300	15	4	Ø25	1-Phase 0,5 HP 3-phase 0,6 HP
T-40/FL	900	54 HL/h	355x550x600	29	3	Ø40	1-Phase 0,8 HP 3-phase 1,0 HP
T-70/FL	900	63 HL/h	370x660x620	20	3	Ø40	1-Phase 1,10 HP 3-phase 1,10 HP
T-110/FL	900	120 HL/h	330x700x680	37	3	Ø50	1-Phase 2,1HP 3-phase 1,5 HP
T-180/FL	900	260 HL/h	820x420x780	50	3	Ø60	3-phase 2,1 HP